






Technical drawing of the A-CE valve assembly. The drawing shows a side view of the valve with a handle on the left and a threaded port on the right. Dimensions are indicated with arrows and numbers: 40 (total width), 18.5 (distance from handle to center), 10 (distance from center to port), and 48.5 (total length). A label 'A-CE' is on the valve body. A label 'トレードマーク' (Trademark) points to the A-CE logo. A label 'PT1/8' points to the threaded port.



部品表				
番号	数量	部品名	材料	説明
01	1	本体	C3771(cd75ppm以下)	Ep-Cu/Ni,Cr
02	1	ソケット	C3604(cd75ppm以下)/SUS	Ep-Cu/Ni,Cr
03	1	ステム	C3604(cd75ppm以下)	
04	1	ハンドル	PBT	オレンジ色
05	2	シート	PTFE	
06	1	ボール	C3604(cd75ppm以下)	Ep-Cu/Ni,Cr
07	2	Oリング	NBR-70-1	
08	1	リンフ	C2680	
09	1	ビス	STEEL	三価クロメート
21	1	キャップ	PBT	オレンジ色



使用圧力		MAX 0.98MPa	
使用温度		-10℃～+80℃(凍結無き事)	
※バルブ構成材質に影響のない環境下で(流体を含む)ご使用下さい。 ※使用圧力や使用温度等は、諸条件に寄って変動が生じます。			
		第3角法	単位 mm 尺度 1:1 日付 2018/02/08
承認	水田	検図	水田
設計	水田	製図	浅生
		品名・品番	
		エースボール BC-1106R	
		図番	
		1R-BC1106	